


## Automotive high voltage power Schottky rectifier



### Features

- AEC-Q101 qualified
- Negligible switching losses
- High junction temperature capability
- Low leakage current
- Good trade off between leakage current and forward voltage drop
- Avalanche capability specified
- ECOPACK<sup>®</sup>2 compliant component
- PPAP capable
- $V_{RRM}$  guaranteed from  $-40^{\circ}\text{C}$  to  $+175^{\circ}\text{C}$

### Description

Schottky rectifiers packaged in SMA or SMB, and designed for high frequency miniature switched mode power supplies as DC/DC converters for automotive applications. It is particularly suited for LED lighting applications, ADAS power, and ECU (Engine Control Unit) in automotive environment.

Product status	
STPS1H100-Y	
Product summary	
Symbol	Value
$I_{F(AV)}$	1 A
$V_{RRM}$	100 V
$T_j$ (range)	$-40^{\circ}\text{C}$ to $+175^{\circ}\text{C}$
$V_{F(max.)}$	0.62 V

# 1 Characteristics

**Table 1. Absolute ratings (limiting values at 25 °C, unless otherwise specified)**

Symbol	Parameter		Value	Unit	
$V_{RRM}$	Repetitive peak reverse voltage, $T_j = -40\text{ °C to }+175\text{ °C}$		100	V	
$I_{F(RMS)}$	Forward rms current		10	A	
$I_{F(AV)}$	Average forward current, $\delta = 0.5$	SMA $T_L = 150\text{ °C}$	1	A	
		SMB $T_L = 155\text{ °C}$			
$I_{FSM}$	Surge non repetitive forward current		$t_p = 10\text{ ms sinusoidal}$	50	A
$P_{ARM}$	Repetitive peak avalanche power		$t_p = 10\text{ }\mu\text{s}, T_j = 125\text{ °C}$	108	W
$T_{stg}$	Storage temperature range		-65 to +175	°C	
$T_j$	Maximum operating junction temperature <sup>(1)</sup>		+175	°C	

1.  $(dP_{tot}/dT_j) < (1/R_{th(j-a)})$  condition to avoid thermal runaway for a diode on its own heatsink.

**Table 2. Thermal parameters**

Symbol	Parameter		Max. value	Unit
$R_{th(j-l)}$	Junction to lead	SMA	30	°C/W
		SMB	25	

**Table 3. Static electrical characteristics**

Symbol	Parameter	Test conditions		Min.	Typ.	Max.	Unit
$I_R^{(1)}$	Reverse leakage current	$T_j = 25\text{ °C}$	$V_R = V_{RRM}$	-		4	$\mu\text{A}$
		$T_j = 125\text{ °C}$		-	0.2	0.5	mA
$V_F^{(2)}$	Forward voltage drop	$T_j = 25\text{ °C}$	$I_F = 1\text{ A}$	-		0.77	V
		$T_j = 125\text{ °C}$		-	0.58	0.62	
		$T_j = 25\text{ °C}$	$I_F = 2\text{ A}$	-		0.86	
		$T_j = 125\text{ °C}$		-	0.65	0.70	

1. Pulse test:  $t_p = 5\text{ ms}, \delta < 2\%$


2. Pulse test:  $t_p = 380\text{ }\mu\text{s}, \delta < 2\%$

To evaluate the conduction losses, use the following equation:


$$P = 0.54 \times I_{F(AV)} + 0.08 \times I_{F(RMS)}^2$$

### 1.1 Characteristics (curves)


**Figure 1. Average forward power dissipation versus average forward current**




**Figure 2. Average forward current versus ambient temperature ( $\delta = 0.5$ )**




**Figure 3. Normalized avalanche power derating versus junction temperature ( $T_j = 125$  °C)**




**Figure 4. Relative variation of thermal impedance junction to ambient versus pulse duration (SMA)**




**Figure 5. Relative variation of thermal impedance junction to ambient versus pulse duration (SMB)**




**Figure 6. Reverse leakage current versus reverse voltage applied (typical values)**




**Figure 7. Junction capacitance versus reverse voltage applied (typical values)**




**Figure 8. Forward voltage drop versus forward current (maximum values)**



**Figure 9. Thermal resistance junction to ambient versus copper surface under each lead (SMB)**



**Figure 10. Thermal resistance junction to ambient versus copper surface under each lead (SMA)**




## 2 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: [www.st.com](http://www.st.com). ECOPACK® is an ST trademark.

### 2.1 SMB package information

- Epoxy meets UL94, V0
- Lead-free package


**Figure 11. SMB package outline**



**Table 4. SMB package mechanical data**

Ref.	Dimensions			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A1	1.90	2.45	0.0748	0.0965
A2	0.05	0.20	0.0020	0.0079
b	1.95	2.20	0.0768	0.0867
c	0.15	0.40	0.0059	0.0157
D	3.30	3.95	0.1299	0.1556
E	5.10	5.60	0.2008	0.2205
E1	4.05	4.60	0.1594	0.1811
L	0.75	1.50	0.0295	0.0591


**Figure 12. SMB recommended footprint**



## 2.2 SMA package information

- Epoxy meets UL94, V0
- Lead-free package


**Figure 13. SMA package outline**



**Table 5. SMA package mechanical data**

Ref.	Dimensions			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A1	1.90	2.45	0.075	0.097
A2	0.05	0.20	0.002	0.008
b	1.25	1.65	0.049	0.065
c	0.15	0.40	0.006	0.016
D	2.25	2.90	0.089	0.114
E	4.80	5.35	0.189	0.211
E1	3.95	4.60	0.156	0.181
L	0.75	1.50	0.030	0.059

Figure 14. SMA recommended footprint in mm (inches)





### 3 Ordering Information

**Table 6. Ordering information**

Order code	Marking	Package	Weight	Base qty.	Delivery mode
STPS1H100AY	S11Y	SMA	0.068 g	5000	Tape and reel
STPS1H100UY	G11Y	SMB	0.107	2500	

## Revision history

**Table 7. Document revision history**

Date	Version	Changes
3-Dec-2010	1	Initial release.
10-Apr-2018	2	Update Figure 3 "Normalized avalanche power derating versus pulse duration" with $P_{ARM}$ 10 $\mu$ s curve.

**IMPORTANT NOTICE – PLEASE READ CAREFULLY**

STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST’s terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers’ products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2018 STMicroelectronics – All rights reserved