








Card Connectors (SIM, CF, MicroDIMM, PCIe, MXM)

Series	SF7	SF8	SF9	JC26C2	WA6	MM60	MM70
Photo							
Card	SIM/SAM	SIM	SIM	CF	MicroDIMM	PCI Express Mini Card	MXM3.0 Graphics Board
Mounted Height	1.9, 2.3, 2.5mm	1.55mm	1.8mm	5.8, 7.4mm	3.0mm	3.9, 5.9mm	4.3, 6.7mm
Pin Count	6, 6+2	6	6	50	214	52	314
Current Rating	10 μ A to 1A	10 μ A to 1A	10 μ A to 1A	0.5A	0.3A	0.5A	0.5A
Durability	5,000 cycles	5,000 cycles	5,000 cycles	10,000 cycles	25 cycles	50 cycles	30 cycles
Style	Hinged	Tray type	Tray type	Ejector	Board to board	Module socket	Module socket
Features	Locked structure. Positioning boss or metal cover available.	Lowest profile for tray type connector. Normal and reverse mount available.	Normal and reverse mount available. 5 hold downs for EMI and ESD prevention.	Reverse mount avail. Retractable ejector avail.	DDR2 MicroDIMM JEDEC Standard MO-260B SO-004A	Retention latch part available to fix module to connector.	Redesigned positioning stopper prevents contact failure.



Compact Flash:

Frame: **JC26C2 - D S R E**D: Push-push ejector
F: Fixed ejectorS: Standard
R: Reversed

16: +1.6mm

R: Right, flip
L: Left, flip
M: Right, fixed
H: Left, fixedSIM: **SF7W 006 S 1 A**006: 6 position
008: 6 signal + 2 switchA: Positioning boss
B: No boss
E: Low profile1: Standard
4: Low profile

DDR2 MicroDIMM:

Female side: **WA6F214VA1T**Male side: **WA6M214VA1T**SIM: **SF8V006S4AR1200**Slide type
connectorA: Standard
B: Reverse

Only orderable in reels

Tray for: **SF8-STS1-A** Standard
SF8-STR1-B Reverse**Need both Connector and Tray to use SF8 series**SIM: **SF9W006S4AR1200**Slide type
connectorA: Standard
B: Reverse

Only orderable in reels

Tray for: **SF9-STS1-A** Standard
SF9-STR1-B Reverse**Need both Connector and Tray to use SF9 series**

Express Mini Card:

Connector: **MM60 - 52 - B 1 - E 1**

No. of contacts

Socket type

Key type

Contact
finishHeight
modification
codeLatch: **MM60 - EZ - H059 - B 5**

Latch type

Connector height

With boss

5: Sn
plating

MXM 3.0 Graphics Card

Connector: **MM70-314-310B 1 - 1**

Height code:

1: 6.7mm
2: 4.3mm

Gold Plating Thickness

1: 0.1µm
2: 0.3µm

Other Product Offerings

Board-to-Board



Input/Output



Board-to-Flex



Board-to-Cable



Circular



Transportation

