

Ceramic Surface Mount Frequency Mixer WIDE BAND

SIM-43MH+

Level 13 (LO Power +13 dBm) 824 to 4200 MHz



Generic photo used for illustration purposes only

CASE STYLE: HV1195

Maximum Ratings


Operating Temperature	-40°C to 85°C
Storage Temperature	-55°C to 100°C
RF Power	50mW

For extended temperature range, consult factory.
Permanent damage may occur if any of these limits are exceeded.

Pin Connections

LO	8
RF	4
IF	2
GROUND	1,3,5,6,7


Outline Drawing



Outline Dimensions (inch/mm)

A	B	C	D	E	F	G
.200	.180	.087	.025	.050	.028	.043
5.08	4.57	2.2098	0.64	1.27	0.71	1.09
H	J	K	L	M	N	wt
.050	.030	.043	.204	.127	0.065	grams
1.27	0.76	1.09	5.18	3.23	1.65	0.08

Demo Board MCL P/N: TB-382 Suggested PCB Layout (PL-239)



- NOTES:
- TRACE WIDTH AND GAP ARE SHOWN FOR ROGERS RO4350B WITH DIELECTRIC THICKNESS .020" ± .0015"; COPPER: 1/2 OZ. EACH SIDE.
FOR OTHER MATERIALS TRACE WIDTH AND GAP MAY NEED TO BE MODIFIED.
 - BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.
-

Notes

- Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- The parts covered by this specification document are subject to Mini-Circuit's standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuit's website at www.minicircuits.com/WCLStore/terms.jsp

Features

- wide bandwidth, 824 to 4200 MHz
- low conversion loss, 6.1 dB typ.
- excellent L-R isolation, 35 dB typ.
- LTCC double balanced mixer
- tiny size, low profile, 0.08"
- useable as up and down converter
- aqueous washable
- protected by US patent 7,027,795

Applications

- cellular
- defense & weather radar
- defense communications
- PCN
- WCDMA
- WIFI
- blue tooth
- VSAT
- ISM

Electrical Specifications

FREQUENCY (MHz)	CONVERSION LOSS* (dB)			LO-RF ISOLATION (dB)		LO-IF ISOLATION (dB)		IP3 at center band (dBm)
	LO/RF $f_c - f_u$	IF		Typ.	Min.	Typ.	Min.	
824-4200	DC-1500	Typ.	σ	Max.	Typ.	Min.	Typ.	Min.
824-2500		6.3	0.1	8.3	37	26	24	10
2500-4200		5.7	0.1	9.8	30	22	20	14


1 dB Compression: +9 dBm typ.









* Conversion loss at 30 MHz IF. σ is a measure of repeatability from unit to unit.

Typical Performance Data

Frequency (MHz)	Conversion Loss (dB)	Isolation L-R (dB)	Isolation L-I (dB)	VSWR RF Port (:1)	VSWR LO Port (:1)
750.00	780.00	7.46	39.30	2.20	8.86
825.00	855.00	6.69	35.94	2.30	4.77
900.00	930.00	6.56	35.28	2.31	3.65
975.00	1005.00	6.87	37.48	2.51	2.65
1050.00	1080.00	6.25	41.33	2.47	2.12
1125.00	1155.00	5.97	45.94	2.97	1.81
1200.00	1230.00	5.82	52.76	31.04	1.53
1275.00	1305.00	6.05	46.72	31.39	1.29
1350.00	1380.00	6.05	42.28	35.10	1.13
1425.00	1455.00	5.78	39.40	38.15	1.19
1500.00	1530.00	5.68	37.98	39.15	1.37
1800.00	1830.00	5.78	37.32	21.79	1.67
2100.00	2130.00	5.75	34.21	14.00	1.88
2400.00	2430.00	5.36	31.94	17.74	2.36
2700.00	2730.00	5.77	30.66	23.65	2.04
3000.00	3030.00	5.61	29.22	29.71	1.72
3360.00	3390.00	5.94	28.61	24.35	1.80
3540.00	3570.00	6.60	26.65	22.73	2.36
4080.00	4110.00	7.87	26.87	19.22	4.21
4260.00	4290.00	8.69	27.67	19.60	5.88

Electrical Schematic





Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp

